IOP Conf. Series: Earth and Environmental Science 780 (2021) 012014

# Rule of thumb for the calculation of overall transfer thermal value in Bandung

L Kusumawati<sup>1,2</sup>\*, E Setyowati<sup>3</sup> and A B Purnomo<sup>1</sup>

<sup>1</sup> Lecturer at Department of Architecture, Faculty of Civil Engineering and Planning, Trisakti University, Jakarta, Indonesia

<sup>2</sup> Student of Doctoral Program in Architecture and Urban Science, Diponegoro University, Semarang, Indonesia

<sup>3</sup> Lecturer at Departement of Architecture, Faculty of Engineering, Diponegoro University, Semarang, Indonesia

\*lili.kusumawati@trisakti.ac.id

Abstract. The rule of thumb for heat transfer in building envelopes is made to make it easier to calculate heat transfer using the OTTV formula from SNI. Using this formula, it often makes it difficult for architects to quickly estimate the heat transfer value of a building. The OTTV formula variable issued by SNI is not an architectural design variable. Only one variable that is in accordance with the field of architecture is the window to wall ratio (WWR). The use of the OTTV formula is very dependent on the location of the building and solar radiation. So to overcome this difficulty, the researcher tries to offer a rule of thumb formula for calculating heat transfer. To get the OTTV formula by rule of thumb by means of design variable regression. With the rule of thumb formula for calculating OTTV, it is hoped that it can make it easier for architects to consider designs that are adapted to local conditions.

#### 1. Introduction

The Buildings contribute a lot to the increased heat in their environment which results in increasing temperatures in the building. From a number of cities, for example, Jakarta, where daily temperatures range from 27 °C to 33 °C, humidity ranges from 50% to 70%, wind speed which is almost always 0 m /s. With such high temperature and humidity, it is often difficult to make buildings cool. Especially if the air circulation is not enough, then to make the space comfortable, the user will solve it by turning on the air conditioner. In such conditions, if the building is designed following the principles of energyefficient building, the use of artificial ventilation can be reduced [1].

Many buildings pay less attention to the local climate, even though the surrounding climate and indoor conditions have a big impact on the energy performance of the building. Likewise, the orientation of the building face and the materials used in the building envelope can cause solar radiation to affect the cooling load and lighting design of buildings [2].

One of the building components commonly affected by the external environment is the building envelope, with thermal energy commonly transferred through its transparent and non-transparent walls and roofs [3,4]. Therefore, it is necessary to determine the performance of the building, in accordance with the thermal carried by sunlight through the building envelope. This is because some designs such

Content from this work may be used under the terms of the Creative Commons Attribution 3.0 licence. Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI. Published under licence by IOP Publishing Ltd 1

3rd International Seminar on Livable Space	IOP Publishing
IOP Conf. Series: Earth and Environmental Science 780 (2021) 012014	doi:10.1088/1755-1315/780/1/012014

as double skin/glass, absorbing, and reflective glass, adding horizontal, vertical, and egg-crate overhang aid in conducting thermal transfer [5,6].

According to several studies, the right building orientation produces good thermal performance. Similarly, increasing the building's width helps to decrease the amount of sun's rays that enters the rooms, thereby, obtaining a more comfortable thermal performance. However, the thickness of the walls did not contribute to a significant reduction in the temperature of the interior space [7]. Regarding the use of materials, the proper shape of the building envelope has the ability to reduce room temperature and save energy with ease of workmanship, efficiency, maintenance costs, and minimum OTTV [8,9]. The local climate needs to be considered while developing the building's envelope shape, type, and material because it greatly impacts the comfort inside the building. Therefore, with the use of the right type of sheath in hot, dry, humid, or very hot climates, the cooling load tends to decrease [10]. Horizontal, vertical, and grid types of building to Chua, et al. the sheath that acts as the shading device is suitable for buildings facing north and south, while horizontal overhangs inclined at 30° downward are suitable for east and west region [13]. But another opinion states that diagonal building envelopes are better than vertical and egg-crate in reducing room temperature [14]. Generally, it was found that there is no common method used to access the building envelope [15].

The amount of thermal transfer value is calculated by the OTTV formula, which is an index used to compare the performance of buildings. It consists of three main components, namely [3]: (a) conduction through a massive wall ( $\alpha[(Uw \times (1 - WWR) \times (TDek]))$ , (b) conduction through a transparent wall  $(Uf \times WWR \times \Delta T)$ , (c) solar radiation through the glass ( $SC \times WWR \times SF$ ). The overall thermal transfer value of the exterior wall and the roof transfer thermal value (RTTV) are commonly determined. According to the OTTV regulation from SNI: 2011, all buildings that use artificial ventilation need to be designed with a maximum value of 35w / m2.

This formula is written as follows:

$$OTTV = (\alpha[(Uw \times (1 - WWR) \times TDek]) + (Uf \times WWR \times \Delta T) + (SC \times WWR \times SF)[3].$$

Where,

OTTV: Overall thermal transfer value (W/m<sup>2</sup>)

- A : Abstorttance of solar radiation
- Uw : Thermal transmittance of opaque wall  $(W/m^2.K^\circ)$
- WWR: Window to wall ratio
- TDek : Equivalent temperature difference (K)
- Uf : Thermal transmittance of fenestration  $(W/m^2.K^\circ)$
- $\Delta T$  : Temperature difference between exterior and interior design conditions (5°K)
- SC : Shading coefficient of fenestration (where  $SC = SCeff \times SCglass$ )
- SF : Solar factor  $(W/m^2)$

WWR is always present in the three main components listed above. It plays an important role in OTTV calculations. Besides that, to respond to climate change that is getting hotter, Ruey, et al. Have taken an approach in changing the OTTV index [16]. For example, it can be seen in some formulas used in Hong Kong and Taiwan in calculating the heat transfer entering the building [16,17].

Besides WWR, another important variable is the value of SC and SF [3]. SC is related to design, however, obtaining its value is quite complicated. This is because, the architects needs to carefully analyze the pieces in the CAD drawings by measuring the width ratio of the overhang projection factor (OPF) to the surface exposed to sunlight. From the OPF value, the SC is obtained, as shown in the SNI: 2011 table. This makes it easy for the value to be directly used, however, assuming there is no exact value in the table, the interpolation method is used for its calculation.

SC values are also used in the Ecotect program, which was originally modeled to determine the value of the shading coefficient of the fenestration system. After the model is made, on the transparent (glass) part, the SC value is located on the tap. Users are advised to click to calculate SC, and in the SunPath

diagram with the time adjusted to 21st March, June, September, and December. This is followed by clicking on the tab and exporting to Ms. excel sheet, from there, the normal direct radiation is obtained according to the angle of the sun in accordance with SNI [3]. Therefore, architects are likely to acquire an average SC value in a year. The SF values used to determine the location variables are more complicated to obtain. This is because it needs to explore the distribution of sunlight obtained from the climatological aspects.

In addition, expertise is needed to calculate the amount of sun's thermal transfer value into the building, even though the subject is less familiar to an architect. Therefore, in designing a building, an architect or student needs to possess adequate knowledge of the thermal transfer problem design building envelopes that meet green standards. The use of the OTTV SNI: 2011 formula often makes it difficult for users to quickly estimate the value of building thermal transfer, especially for amateurs. The formula makes it difficult for users, especially an architecture student trying to determine the right energy needed for the building. The OTTV formula variable issued by SNI is not an architectural design, and therefore, it is new to architects. The only variant that fits the architecture field is WWR, which is the ratio of the window area to the entire outer wall in the orientation specified. The use of the OTTV formula depends on the location of the building and the sun's radiation.

The rule of thumb for one-sided ventilation in buildings is carried out in the field of architecture. For spaces with access to only one facade, ventilation on one side works to a maximum depth of 6.00 m. Windows are used because they provide ventilation and sunlight. The opening area is at least 5% of the ventilated floor, and it is more in hot climate regions with low wind speeds [18]. The construction sector uses a lot of rules of thumb over other technology sectors such as a beam with a span of 4.00 m and a height of  $1/20 \times 3.50 \text{ m} = 0.175 \text{ m}$ . In the era of design, with the help of computers, CAD, and building information modeling (BIM), the rule of thumb remains an invaluable verification tool [19,20]. It comprises of simple principles, which are generally reliable, and provide a broad view of how to achieve goals [21]. It is defined as a set of principles based on experience [22]. Rule of thumb is more reliable based on scientific experiments with efforts taken to clarify most of the assumptions [23].

Therefore, to overcome the difficulties faced by the use of the OTTV-SNI: 2011 formula by the architect, the rule of thumb formula was developed by utilizing WWR in line with other countries.

## 2. Material and methods

The object to be studied is the building envelope in C, the use of this building is only as a basic idea by taking one bay which is then simulated. Building C is a faculty building with mixed activities (office, study room, library and laboratory). The building was taken to represent the buildings on the Trisakti University campus, and because it has a distinctive character that is almost equilateral with two faces (north and south) with an overhang without louvers as sun protection and the other two faces (west and east) with an overhang equipped with louvers. Building C was drawn using CAD with one bay drawn from a column to another. One bay is simulated with various forms of shading device and produce various forms of the facade, which are variables of OTTV. This research uses model simulation, for example Karim, et al. Have simulated 54 windows to get the heat gain value [24].

The basis for calculating OTTV is to use the standard SNI 6389: 2011 - Energy Conservation of Building Envelopes in Buildings. It also requires data on the building materials used, absorption value, thermal transmittance, equivalent temperature, solar factor, and the value of SCef (shading coefficients effective). Effective SC is obtained from SC glass multiplied by SC from the OPF-overhead project factor or SPF-sidefin project factor. In this calculation the building material is not changed, what is changed in various alternatives is the design of the shading device. To calculate OTTV is quite complicated, then this OTTV formula will then be simplified by means of the rule of thumb.

IOP Conf. Series: Earth and Environmental Science 780 (2021) 012014 doi:10.1088/1755-1315/780/1/012014



Figure 1. Building C on campus A of Trisakti University.



Plastered bricks in shiny white paint



IOP Conf. Series: Earth and Environmental Science 780 (2021) 012014

doi:10.1088/1755-1315/780/1/012014



Figure 3. Example of multiple pieces of window unit.

To obtain the OTTV rule of thumb from WWR, the following were carried out:

First, make a simulation bay in the facade of 300 cases; The facade is designed based on the configuration of the variables, such as WWR, which was randomly obtained; WWR is considered an independent variable. OTTV is calculated using the OTTV-SNI: 2011 formula, which is considered a dependent variable. Then, to obtain the OTTV rule of thumb = WWR function curve estimation method is used from SPSS 26.0. When a stepwise regression is made, the best rule of thumb is taken from the regression equation with the largest R square value.

#### 3. Results and discussion

1

From the stepwise regression analysis, the results are as follows:

Model     Variables Entered     Variables Removed     Method       1     WWR     .     Stepwise (Criteria: Probability-of-F-to- enter <= 050				
1 WWR . Stepwise (Criteria: Probability-of-F-to- enter <= 050 Probability-of-F-to-remov	Model	Variables Entered	Variables Removed	Method
>= .100).	1	WWR		Stepwise (Criteria: Probability-of-F-to- enter <= .050, Probability-of-F-to-remove >= .100).

Table 1. Variables entered/removed<sup>a</sup>

a. Dependent Variable: OTTV-SNI

			-	
Model	R	R Square	Adjusted R Square	Std. Error of the Estimate
1	.918ª	.843	.843	4.00910254

 Table 2. Model summary.

a. Predictors: (Constant), WWR

IOP Conf. Series: Earth and Environmental Science 780 (2021) 012014 doi:10.1088/1755-1315/780/1/012014

·	Madal	Unstandardiz	ed Coefficients	Standardized Coefficients		C: a
Wodel –	В	Std. Error	Beta	t		
1	(Constant)	7.137	.555		12.863	.000
	WWR	102.657	2.565	918	40.030	.000

Table 3. Coefficients<sup>a</sup>

a. Dependent Variable: OTTV-SNI

From the stepwise regression, the result is R = 0.918, then the rule of thumb formula is obtained as follows:

$$OTTV = 7.137 + 102.657 \times WWR$$

Of the 30 cases of facades that were not used to produce a rule of thumb above, it was obtained RMSE (root meaning square error) = 0.50 with an error factor = 0%.

#### 4. Conclusion

The formula for a rule of thumb with OTTV as a WWR function has been obtained; it is hoped that this rule of thumb will be useful for architects and students in calculating OTTV on facade designs; this rule only applies in Bandung, therefore a similar study is needed for other cities in Indonesia. By using the rule of thumb formula for  $OTTV = 7.137 + 102.657 \times WWR$ , the architects can find out the OTTV from their design, so their work has filled the green building.

### Acknowledgment

The authors are grateful to Trisakti University, for the opportunity to participate in a doctoral program in Architecture and Urban Planning at Diponegoro University - Semarang.

#### References

- [1] Karyono T H 2010 Green Architecture: Pengantar Pemahaman Arsitektur Hijau Di Indonesia (Rajawali Pers)
- [2] Karyono T H 2013 Arsitektur dan Kota Tropis Dunia Ketiga (Jakarta: Rajawali Pers)
- [3] BSN 2011 SNI 03-6389-2011 Konservasi energi selubung bangunan pada bangunan gedung. 1.
- [4] Jakarta Provincial Government 2016 Jakarta Green Building User Guide : Building Envelope 1
- [5] Arq R and Jun C 2014 Performance and style in the work of Olgyay and Olgyay 2 2014–5
- [6] Olgyay V 1992 Design with Climate: Bioclimatic Approach to Architectural Regionalism (New York, USA: Van Norstrand Reinhold)
- [7] Ardiyanto A 2015 Strategi Arsitektural Dalam Penentuan Kinerja Termal Pada Bangunan Kantor Kolonial Semarang (UGM)
- [8] Kusumawati L K 2015 The Influence of Facade Design on Energy Efficiency *Prosiding Seminar Nasional "Is Livas"* (Jakarta) pp 106–19
- [9] Machdijar L K, Setyowati E and Purnomo A B 2019 Anticipation of solar radiation through the building C envelope of campus a Universitas Trisakti *AIP Conf. Proc.* **2114**
- [10] Kirimtat A, Koyunbaba B K, Chatzikonstantinou I and Sariyildiz S 2016 Review of simulation modeling for shading devices in buildings *Renew. Sustain. Energy Rev.* 53 23–49
- [11] Jinkyun Choa; Changwoo Yoob; Yundeok Kim 2014 Viability of exterior shading devices for high-rise residential buildings: Case study for cooling energy saving and economic feasibility analysis *Energy Build*. 82 771–85
- [12] Kusumawati M. L 2016 SHADING DEVICE DESIGN BASED ON SUN POTITION AND INDOOR LIGHTING REQUIREMENTS International Seminar Livable Space Applying Local Knowledge for Livable Space (Jakarta: Dept.of Architecture, Faculty of Civil Engineering and Planing, Trisakti University) pp 193–8
- [13] Baek S and Park J C 2016 Fundamental Study on the Optimal Design of a Folding Shading

IOP Conf. Series: Earth and Environmental Science 780 (2021) 012014 doi:10.1088/1755-1315/780/1/012014

Device : Solar Radiation Model & Potential Cooling Load Saving focusing on analyzing the effects of cooling load reduction through computer simulation for the system 335–41

- [14] Ahmed A. Y Freewan and Freewan A A Y 2011 Improving Thermal Performance Of Offices In JUST Using Fixed Shading Device. 1860–6
- [15] Bellia L, Marino C, Minichiello F and Pedace A 2014 An overview on solar shading systems for buildings *Energy Procedia* 62 309–17
- [16] Hwang R L, Shih W M, Lin T P and Huang K T 2018 Simplification and adjustment of the energy consumption indices of office building envelopes in response to climate change Appl. Energy 230 460–70
- [17] Hui S C M 1997 Overall Thermal Transfer Value (OTTV): How to Improve Its Control in Hong Kong
- [18] Heywood H 2019 101 Rules of Thumb For Low Energy Architecture ed J Thomson (London: RIBA Publishing)
- [19] Schodek D L 1992 Structure (New Jersey, USA: Prentice-Hall, Inc)
- [20] Czarnecki L and Van Gemert D 2016 Scientific basis and rules of thumb in civil engineering: Conflict or harmony? *Bull. Polish Acad. Sci. Tech. Sci.* **64** 665–73
- [21] Connell A O, Edgar C, Convenor C O, Mussett D, Benbow J and Prisk K 2016 Decumulation Options in the New Zealand Market: How Rules of Thumb can help A paper for the 20th Biennial Conference of the New Zealand Society of Actuaries by: For correspondence: Christine Ormrod, Convenor of the Retirement Income Interest Group Thi
- [22] Reinhart C F 2005 A simulation-based review of the ubiquitous window-headheight to daylit zone depth rule-of-thumb *IBPSA 2005 Int. Build. Perform. Simul. Assoc. 2005* 1011–8
- [23] Lukman N, Ibrahim N, Hayman S and Hyde R 2009 Rule of thumb for daylighting of rooms with external obstructions *Archit. Sci. Rev.* **52** 151–60
- [24] Karim M A, Hasan M M and Khan M I H 2019 A simplistic and efficient method of estimating air-conditioning load of commercial buildings in the sub-tropical climate *Energy Build*. **203**