

**LEMBAR
HASIL PENILAIAN SEJAWAT SEBIDANG ATAU PEER REVIEW
KARYA ILMIAH : PROSIDING**

Judul Karya Ilmiah (Prosiding) : Zeolite/Magnetite Composites as Catalyst on the Synthesis of Methyl Ester (MES) from Cooking Oil

Nama/ Jumlah Penulis : Sriatun, Adi Darmawan, Sriyanti, Wuri Cahyani, Hendri Widyandari

Status Pengusul : Penulis pertama

Identitas Prosiding :

- a. Judul Prosiding : IOP Conference Series: Journal of Physics
- b. ISBN/ISSN : 1742-6588, E-ISSN: 1742-6596
- c. Thn Terbit, Tempat Pelaks. : 2018/1025/012135
- d. Penerbit/Organiser : IOP Publishing
- e. Alamat Repository/Web : <https://iopscience.iop.org/journal/1742-6596>
- Alamat Artikel : <https://iopscience.iop.org/article/10.1088/1742-6596/1025/1/012135/pdf>
- Url Turnitin (9%) : [http://eprints.undip.ac.id/80669/26/C26_Zeolitemagnetite_composites_as_catalysts_on_the_Synthesis_of_Methyl_Esters_\(MES\)_from_cooking_oil.pdf](http://eprints.undip.ac.id/80669/26/C26_Zeolitemagnetite_composites_as_catalysts_on_the_Synthesis_of_Methyl_Esters_(MES)_from_cooking_oil.pdf)

f. Terindeks di (jika ada) : SCOPUS (SJR 0,221)

Kategori Publikasi Makalah : ☒ Prosiding Forum Ilmiah Internasional
(beri ✓ pada kategori yang tepat) ☐ Prosiding Forum Ilmiah Nasional

Hasil Penilaian *Peer Review*:

Komponen Yang Dinilai	Nilai Maksimal Prosiding		Nilai Akhir Yang Diperoleh
	Internasional <input checked="" type="checkbox"/>	Nasional <input type="checkbox"/>	
a. Kelengkapan unsur isi prosiding (10%)	3		3
b. Ruang lingkup dan kedalaman pembahasan (30%)	9		9
c. Kecukupan dan kemutakhiran data/informasi dan metodologi (30%)	9		8,6
d. Kelengkapan unsur dan kualitas terbitan /prosiding (30%)	9		8,6
Total = (100%)	30,00		29,2
Penulis Utama: 0,6 x 29,2 = 17,52			

Catatan Penilaian Paper oleh Reviewer :

- Kesesuaian dan kelengkapan unsur isi prosiding:**
Paper ini telah berisi unsur-unsur penting dalam karya ilmiah, hubungan antara judul, abstrak, pendahuluan sampai pembahasan telah sesuai. Nilai 3
- Ruang lingkup dan kedalaman pembahasan:**
Ruang lingkup tentang komposit zeolit/magnetit sebagai katalis dalam sintesis MES dari minyak goreng bekas. Pembahasan dibahas dengan baik dan detail. Nilai 9
- Kecukupan dan kemutakhiran data/informasi dan metodologi:**
Data disampaikan dengan baik dan lengkap dan cukup mutakhir, metodologi cukup detail. Nilai 8,6
- Kelengkapan unsur dan kualitas terbitan/prosiding:**
Unsur terbitan lengkap, kualitas terbitan prosiding cukup baik. Nilai 8,6

Semarang, 3 April 2020
Reviewer 1



Dr. Bambang Cahyono, MS
NIP. 196303161988101001
Unit Kerja : Departemen Kimia FSM UNDIP

**LEMBAR
HASIL PENILAIAN SEJAWAT SEBIDANG ATAU PEER REVIEW
KARYA ILMIAH : PROSIDING**

Judul Karya Ilmiah (Prosiding) : Zeolite/Magnetite Composites as Catalyst on the Synthesis of Methyl Ester (MES) from Cooking Oil

Nama/ Jumlah Penulis : Sriatun, Adi Darmawan, Sriyanti, Wuri Cahyani, Hendri Widyandari

Status Pengusul : Penulis pertama

Identitas Prosiding :

- a. Judul Prosiding : IOP Conference Series: Journal of Physics
- b. ISBN/ISSN : 1742-6588, E-ISSN: 1742-6596
- c. Thn Terbit, Tempat Pelaks. : 2018/1025/012135
- d. Penerbit/Organiser : IOP Publishing
- e. Alamat Repository/Web : <https://iopscience.iop.org/journal/1742-6596>
- Alamat Artikel : <https://iopscience.iop.org/article/10.1088/1742-6596/1025/1/012135/pdf>
- Url Turnitin (9%) : [http://eprints.undip.ac.id/80669/26/C26_Zeolitemagnetite_composites_as_catalysts_on_the_Synthesis_of_Methyl_Esters_\(MES\)_from_cooking_oil.pdf](http://eprints.undip.ac.id/80669/26/C26_Zeolitemagnetite_composites_as_catalysts_on_the_Synthesis_of_Methyl_Esters_(MES)_from_cooking_oil.pdf)

f. Terindeks di (jika ada) : SCOPUS (SJR 0,221)

Kategori Publikasi Makalah : ☒ Prosiding Forum Ilmiah Internasional
(beri ✓ pada kategori yang tepat) ☐ Prosiding Forum Ilmiah Nasional

Hasil Penilaian *Peer Review*:

Komponen Yang Dinilai	Nilai Maksimal Prosiding		Nilai Akhir Yang Diperoleh
	Internasional <input checked="" type="checkbox"/>	Nasional <input type="checkbox"/>	
a. Kelengkapan unsur isi prosiding (10%)	3		3
b. Ruang lingkup dan kedalaman pembahasan (30%)	9		9
c. Kecukupan dan kemutakhiran data/informasi dan metodologi (30%)	9		8
d. Kelengkapan unsur dan kualitas terbitan/prosiding (30%)	9		8
Total = (100%)	30,00		28
Penulis Utama: 0,6 x 28 = 16,8			

Catatan Penilaian Paper oleh Reviewer :

1. Kesesuaian dan kelengkapan unsur isi prosiding:

Unsur isi prosiding lengkap dan sesuai dengan standart IOP Publishing. Nilai 3

2. Ruang lingkup dan kedalaman pembahasan:

Ruang lingkup artikel ini adalah katalis komposit zeolit/magnetit untuk sintesis ME dari minyak goreng bekas dengan keterbaruan yang tinggi. Pembahasan diulas dengan baik (dalam) disertai literatur pendukung. Nilai 9

3. Kecukupan dan kemutakhiran data/informasi dan metodologi:

Data yang disajikan cukup memadai sebagai artikel dan informasi yang disampaikan ada yang tahun kemutakhirannya kurang, metodologi diulas dengan detil sehingga peneliti lain bisa mengulang dengan baik. Nilai 8

4. Kelengkapan unsur dan kualitas terbitan/ prosiding:

Unsur terbitan lengkap, kualitas terbitan ada yang kurang terbaca (gambar) dan salah penulisan (typo). Nilai 8

Semarang, 14 Maret 2020

Reviewer 2

Drs. Gunawan, M.Si, Ph.D

NIP.196408251991031001

Unit Kerja : Departemen Kimia FSM UNDIP

**LEMBAR
HASIL PENILAIAN SEJAWAT SEBIDANG ATAU *PEER REVIEW*
KARYA ILMIAH : PROSIDING**

Judul Karya Ilmiah (Prosiding) : Zeolite/Magnetite Composites as Catalyst on the Synthesis of Methyl Ester` (MES) from Cooking Oil

Nama/ Jumlah Penulis : Sriatun, Adi Darmawan, Sriyanti, Wuri Cahyani, Hendri Widyandari

Status Pengusul : Penulis pertama

Identitas Prosiding :

- a. Judul Prosiding : IOP Conference Series: Journal of Physics
- b. ISBN/ISSN : 1742-6588, E-ISSN:1742-6596
- c. Thn Terbit, Tempat Pelaks. : 2018/1025/012135
- d. Penerbit/Organiser : IOP Publishing
- e. Alamat Repository/Web : <https://iopscience.iop.org/journal/1742-6596>
Alamat Artikel : <https://iopscience.iop.org/article/10.1088/1742-6596/1025/1/012135/pdf>
Url Turnitin (9%) : [http://eprints.undip.ac.id/80669/26/C26_Zeolitemagnetite_composites_as_catalysts_on_the_Synthesis_of_Methyl_Esters_\(MES\)_from_cooking_oil.pdf](http://eprints.undip.ac.id/80669/26/C26_Zeolitemagnetite_composites_as_catalysts_on_the_Synthesis_of_Methyl_Esters_(MES)_from_cooking_oil.pdf)
- f. Terindeks di (jika ada) : **SCOPUS (SJR 0,221)**

Kategori Publikasi Makalah : ☒ Prosiding Forum Ilmiah Internasional
(beri ✓ pada kategori yang tepat) ☐ Prosiding Forum Ilmiah Nasional

Hasil Penilaian *Peer Review* :

Komponen Yang Dinilai	Nilai Reviewer		Nilai Rata-rata
	Reviewer I	Reviewer II	
a. Kelengkapan unsur isi prosiding (10%)	3	3	3
b. Ruang lingkup dan kedalaman pembahasan (30%)	9	9	9
c. Kecukupan dan kemutakhiran data/informasi dan metodologi (30%)	8,6	8	8,3
d. Kelengkapan unsur dan kualitas terbitan/prosiding(30%)	8,6	8	8,3
Total = (100%)	29,2	28	28,6
Penulis Utama(rata-rata): 0,6 x 28,6 = 17,16			


Semarang, 3 April 2020

Reviewer 2



Drs. Gunawan, M.Si, Ph.D
NIP. 196408251991031001
Unit Kerja : Departemen Kimia FSM UNDIP

Reviewer 1



Dr. Bambang Cahyono, MS
NIP. 196303161988101001
Unit Kerja : Departemen Kimia FSM UNDIP

This site uses cookies. By continuing to use this site you agree to our use of cookies. To find out more, see our Privacy and Cookies policy.



PAPER • OPEN ACCESS

The 7th International Seminar on New Paradigm and Innovation on Natural Science and Its Application

Published under licence by IOP Publishing Ltd

Journal of Physics: Conference Series, Volume 1025, The 7th International Seminar on New Paradigm and Innovation on Natural Science and Its Application 17 October 2017, Semarang, Indonesia

2018 *J. Phys.: Conf. Ser.* **1025** 011001

<https://doi.org/10.1088/1742-6596/1025/1/011001>

Buy this article in print

Abstract

PREFACE

The 7th International Seminar on New Paradigm and Innovation on Natural Sciences and Its Application (ISNPINSA-7) is annual conferences organized by Faculty of Sciences and Mathematics (FSM) Diponegoro University and has been successfully conducted since 2011. The aims of ISNPINSA are to facilitate brain storming and state of the art information in field of sciences and mathematics; to increase innovation of technology that can be applied in industries; to contribute in formulating strategy to increase the role of science for community; and to stimulate collaboration between industries, researchers and government to increase community welfare. The theme of 7th ISNPINSA in 2017 is "*Science and Data Science for Sustainable Development Goals*".

The scope of the field of participants comes from various fields including biology, physics, chemistry, statistics, mathematics, informatics, environment, public health, and relevant fields that contribute to sustainable development. The conference was held in Semarang, Indonesia on October, 17th, 2017. There were three keynote speakers and three invited speaker who came from Japan, Italy, Malaysia, Philipines and Indonesia. The number of participants of this seminar were more than 200

consist of researchers, lecturers, postgraduate and undergraduate students from various universities and after the selection process there are 132 articles selected to be published in the present conference proceeding.

The Editors

Dr. Budi Warsito

Sapto Purnomo Putro, Ph.D.

Ali Khumaeni, Ph.D.

Lists of Conference Photographs, Referees, Speakers and Committees are available in this pdf.

Export citation and abstract

[BibTeX](#)

[RIS](#)



Content from this work may be used under the terms of the Creative Commons Attribution 3.0 licence. Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI.

Related content

JOURNAL ARTICLES

Workshop and International Seminar on Science of Complex Natural Systems

Once a physicist: Jon Palfreman

International Seminar on Mathematics and Physics in Sciences and Technology 2017 (ISMAP 2017)

Acknowledgement

Commitment to innovation in publishing

EMMA: a new paradigm in configurable software

PAPER • OPEN ACCESS

The 7th International Seminar on New Paradigm and Innovation on Natural Science and Its Application

To cite this article: 2018 *J. Phys.: Conf. Ser.* **1025** 011001

View the [article online](#) for updates and enhancements.

Related content

- [Workshop and International Seminar on Science of Complex Natural Systems](#)
- [Once a physicist: Jon Palfreman](#)
- [International Seminar on Mathematics and Physics in Sciences and Technology 2017 \(ISMAP 2017\)](#)



IOP | ebooks™

Bringing together innovative digital publishing with leading authors from the global scientific community.

Start exploring the collection—download the first chapter of every title for free.

PREFACE

The 7th International Seminar on New Paradigm and Innovation on Natural Sciences and Its Application (ISNPINSA-7) is annual conferences organized by Faculty of Sciences and Mathematics (FSM) Diponegoro University and has been successfully conducted since 2011. The aims of ISNPINSA are to facilitate brain storming and state of the art information in field of sciences and mathematics; to increase innovation of technology that can be applied in industries; to contribute in formulating strategy to increase the role of science for community; and to stimulate collaboration between industries, researchers and government to increase community welfare. The theme of 7th ISNPINSA in 2017 is “*Science and Data Science for Sustainable Development Goals*”.

The scope of the field of participants comes from various fields including biology, physics, chemistry, statistics, mathematics, informatics, environment, public health, and relevant fields that contribute to sustainable development. The conference was held in Semarang, Indonesia on October, 17th, 2017. There were three keynote speakers and three invited speaker who came from Japan, Italy, Malaysia, Philipines and Indonesia. The number of participants of this seminar were more than 200 consist of researchers, lecturers, postgraduate and undergraduate students from various universities and after the selection process there are 132 articles selected to be published in the present conference proceeding.

The Editors

Dr. Budi Warsito

Sapto Purnomo Putro, Ph.D.

Ali Khumaeni, Ph.D.



CONFERENCE PHOTOGRAPH





LIST OF REFEREES

1. Prof. Widowati
2. Prof. Mustafid
3. Prof. Wahyu Setia Budi
4. Sapto P Putro, PhD
5. Dr. Munifatul Izzati
6. Dr. Budi Warsito
7. Dr. Eng. Ali Khumaeni
8. Dr. Di Asih I Maruddani
9. Dr. Muhammad Nur, DEA
10. Hendri Widyandari, PhD
11. Dr. Kusworo Adi
12. Dr. Heri Sutanto
13. Dr. Endang Kusdiyantini, DEA
14. Dr. Jafron W. Hidayat
15. Rully Rahadian, PhD
16. Anto Budiharjo, PhD
17. Dr. Tri Retnaningsih Soeprbowati
18. Ismiyarto, PhD
19. Dr. Retno Ariadi Lusiana
20. Dr. Tarno, MSi
21. Adi Wibowo, PhD

LIST OF SPEAKERS

Keynote Speaker:

Prof. Dr. Masahiko Tani	University of Fukui, Japan
Prof. Dr. Norsarahaida Saidina Amin	Universiti Teknologi Malaysia
Mario Rosario Guarracino, PhD.	Instituto di Calcolo e Reti ad Alte Prestazioni- National Research Council (ICAR-CNR), Italy
Dr. dr. Budi Wiweko, Sp. OG-KFER.	University of Indonesia, Jakarta

Invited Speaker:

Prof. Elmer S. Estacio, PhD.	National Institute of Physics, University of the Philippines, Manila,
Ismiyarto, S.Si., M.Si., PhD.	Diponegoro University, Semarang, Indonesia
Dr. Eng. Adi Wibowo, S.Si., M.Kom.	Diponegoro University, Semarang, Indonesia

LIST OF COMMITTEES

Steering Committee

Prof. Muhammad Zainuri, Diponegoro University, Indonesia
Prof. Widowati, S.Si., M.Si., Diponegoro University, Indonesia
Prof. Heru Susanto, Diponegoro University, Indonesia
Sapto Purnomo P, Ph.D, Diponegoro University, Indonesia
Drs. Bayu Surarso, M.Sc., Ph.D., Diponegoro University, Indonesia

Scientific Committee

Prof. Norsarahida Saidina Amin, Universiti Teknologi Malaysia
Prof. Dr. Masahiko Tani, University of Fukui, Japan
Mario Rosario Guarracino, Ph.D, ICAR-CNR
Prof. Elmer S. Estacio, University of the Philippines Diliman
Dr. dr. Budi Wiweko, Sp. OG-KFER, University of Indonesia
Prof. Mustafid, Ph.D., Diponegoro University, Indonesia
Prof. Wahyu Setia Budi, Diponegoro University, Indonesia
Dr. Munifatul Izzati, Diponegoro University, Indonesia
Dr. Muhammad Nur, DEA, Diponegoro University, Indonesia
Ismiyarto, Ph.D., Diponegoro University, Indonesia
Adi Wibowo, Ph.D., Diponegoro University, Indonesia

Organizing Committee

Chairman:

Dr. Budi Warsito, M.Si.

Vice Chairman:

Dr. Eng. Ali Khumaeni

Secretary:

Dr. Di Asih I Maruddani, M.Si.

Members:

Yayuk Astuti, Ph.D
Nurdin Bahtiar, S.Si., M.Kom.
Rismiyati, B.Eng, M.Cs.
Pandji Triadyaksa, SSi, M.Sc.
Nur Azizah, SE
Joko Rustianto, S.IP.
Iys Syabilla Rusda, SIP
Fajar Budi Handoyo

Secretariat:

Alik Maulidiyah, M.Sc.

Treasurer:

Titik Eryanti, SE

Choiriyah, SE

Sections**Program:**

Drs. Agus Setyo Utomo, S.Sos, MM & Team

Food:

Dra. Sri Harumaningsih, S.IP. & Team

Papers, Presentations and Proceeding:

Rahmawan Bagus Trianto, S.Kom.

Nur Rohmat, Amd

Transportation and Accomodation:

Deby Yuniarto & Team

Public Relation and Documentation:

Joko Rustianto, S.IP. & Team

This site uses cookies. By continuing to use this site you agree to our use of cookies. To find out more, see our Privacy and Cookies policy.



☐ **NOTICE:** Ensuring subscriber access to content on IOPscience throughout the coronavirus outbreak - see our remote access guidelines.

Table of contents

Volume 1025

2018

◀ Previous issue Next issue ▶

The 7th International Seminar on New Paradigm and Innovation on Natural Science and Its Application 17 October 2017, Semarang, Indonesia

Accepted papers received: 04 May 2018

Published online: 30 May 2018

[View all abstracts](#)

Preface

OPEN ACCESS	011001
The 7th International Seminar on New Paradigm and Innovation on Natural Science and Its Application	

[+ View abstract](#) [View article](#) [PDF](#)

OPEN ACCESS	011002
Peer review statement	

[+ View abstract](#) [View article](#) [PDF](#)

Papers

Material Physics

OPEN ACCESS	012001
Dye-sensitized solar cell simulation performance using MATLAB	

Alvin Muhammad Habieb, Muhammad Irwanto, Ilham Alkian, Fitri Khalimatus Sya'diyah, Hendri Widiyandari and Vincensius Gunawan

OPEN ACCESS

012029

System on chip (SOC) wi-fi microcontroller for multistation measurement of water surface level using ultrasonic sensor

Suryono Suryono, Sapto Purnomo Putro, Widowati and Satriyo Adhy

[+ View abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012030

Analysis of openings and wide of leaf on multileaf Colimators Using Gafchromic RTQA2 Film

Evi Setiawati, Assyifa Lailla Rachma and M. Hidayatullah

[+ View abstract](#) [View article](#) [PDF](#)

Ecology and Biodiversity**OPEN ACCESS**

012031

Potential Re-utilization of Composted Mangrove Litters for Pond Environment Quality Improvement

Endah Dwi Hastuti, Rini Budi Hastuti and Riche Hariyati

[+ View abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012032

The abundance and importance value of tree in "Sendang Kalimah Toyiybah" surrounding and its implication to the spring

Erry Wiryani, Murningsih and Jumari

[+ View abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012033

The invasive alien plants threatened the balance of ecosystem in conservative area in Ontoloe Island, Flores-Indonesia

Ignatius Antonius Mboka Segu Wake, Tri Retnaningsih Soeprbowati and Jumari

[+ View abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012034

Extended benefit cost analysis as an instrument of economic valuated in Petungkriyono forest ecosystem services

Irma Damayanti, Azis Nur Bambang and Tri Retnaningsih Soeprbowati

[+ View abstract](#) [View article](#) [PDF](#)

OPEN ACCESS

012035

The water quality and *Cultivant* enrichment potency of pond based on saprobic index at north coastal waters of Central Java, Indonesia

Application of Inorganic Fertilizer With *NanoChisil* and *Nanosilica* on Black Corn Plant Growth (*Zea Mays* L.)

012128

Lolita Dewi Pertaminaingsih, Erma Prihastanti, Sarjana Parman, Agus Subagio and Ngadiwiyan

[+ View abstract](#)[View article](#)[PDF](#)

OPEN ACCESS

012129

Synthesis of Silicon Carbide Fiber as semiconductor substrate for Betavoltaic cell

Masripah, Agustino Zulys and Jan Setiawan

[+ View abstract](#)[View article](#)[PDF](#)

OPEN ACCESS

012130

Total flavonoid content and formulation antioxidant cream stem of *jatropha multifida* l.

Yuvianti Dwi Franyoto, Lia Kusmita, Mutmainah and Riega Demma Angrena

[+ View abstract](#)[View article](#)[PDF](#)

OPEN ACCESS

012131

Ammonium Removal Efficiency in *Fixed Bed Reactor* and *Suspended Growth Reactor* Using *Ecotru* Inoculation

Rusya Syahidah, Sudarno and Badrus Zaman

[+ View abstract](#)[View article](#)[PDF](#)

OPEN ACCESS

012132

Antioxidant activity from encapsulated Cinnamaldehyde-Chitosan

Bonita Ariestiani, Purbowatingrum, Ngadiwiyan, Ismiyarto, Enny Fachriyah and Khikmah Nurani

[+ View abstract](#)[View article](#)[PDF](#)

OPEN ACCESS

012133

Sulfonated polystyrene and its characterization as a material of electrolyte polymer

Ngadiwiyan, Ismiyarto, Gunawan, RS Purbowatiningrum, N.B.A. Prasetya, T.D. Kusworo and H. Susanto

[+ View abstract](#)[View article](#)[PDF](#)

OPEN ACCESS

012135

Zeolite/magnetite composites as catalysts on the Synthesis of Methyl Esters (MES) from cooking oil

Sriatun, Adi Darmawan, Sriyanti, Wuri Cahyani and Hendri Widyandari

[+ View abstract](#)[View article](#)[PDF](#)

JOURNAL LINKS

[Journal home](#)

N V Danilina and S V Privezentseva 2020 *IOP Conf. Ser.: Mater. Sci. Eng.* **775** 012008

[+ View abstract](#)

[View article](#)

[PDF](#)

Specific features of diaphragm wall construction

D A Mironov *et al* 2020 *IOP Conf. Ser.: Mater. Sci. Eng.* **775** 012051

[+ View abstract](#)

[View article](#)

[PDF](#)

Media technologies in shaping urban identity

T V Karakova *et al* 2020 *IOP Conf. Ser.: Mater. Sci. Eng.* **775** 012038

[+ View abstract](#)

[View article](#)

[PDF](#)

JOURNAL LINKS

[Journal home](#)

[Information for organizers](#)

[Information for authors](#)

[Search for published proceedings](#)

[Contact us](#)

[Reprint services from Curran Associates](#)

JOURNAL HISTORY

2009-present IOP Conference Series: Materials Science and Engineering

doi:10.1088/issn.1757-899X

Online ISSN: 1757-899X

Print ISSN: 1757-8981



Source details

Journal of Physics: Conference Series

Scopus coverage years: from 2005 to Present

Publisher: Institute of Physics Publishing

ISSN: 1742-6588 E-ISSN: 1742-6596

Subject area: [Physics and Astronomy: General Physics and Astronomy](#)

[View all documents >](#)

[Set document alert](#)

[Save to source list](#) [Journal Homepage](#)

CiteScore 2018

0.51



SJR 2018

0.221



SNIP 2018

0.454



[CiteScore](#) [CiteScore rank & trend](#) [CiteScore presets](#) [Scopus content coverage](#)

CiteScore 2018

Calculated using data from 30 April, 2019

$$0.51 = \frac{\text{Citation Count 2018}}{\text{Documents 2015 - 2017}^*} = \frac{11,243 \text{ Citations} >}{21,896 \text{ Documents} >}$$

*CiteScore includes all available document types

[View CiteScore methodology >](#)

[CiteScore FAQ >](#)

CiteScoreTracker 2019

Last updated on 09 April, 2020
Updated monthly

$$0.59 = \frac{\text{Citation Count 2019}}{\text{Documents 2016 - 2018}} = \frac{18,254 \text{ Citations to date} >}{31,135 \text{ Documents to date} >}$$

Metrics displaying this icon are compiled according to Snowball Metrics [↗](#), a collaboration between industry and academia.

CiteScore rank

Category	Rank	Percentile
Physics and Astronomy	#167/216	21st
General Physics and Astronomy		

[View CiteScore trends >](#)

[Add CiteScore to your site](#)

About Scopus

[What is Scopus](#)

[Content coverage](#)

[Scopus blog](#)

[Scopus API](#)

[Privacy matters](#)

Language

[日本語に切り替える](#)

[切换到简体中文](#)

[切换到繁體中文](#)

[Русский язык](#)

Customer Service

[Help](#)

[Contact us](#)



SJR

Scimago Journal & Country Rank

Enter Journal Title, ISSN or Publisher Name

[Home](#)[Journal Rankings](#)[Country Rankings](#)[Viz Tools](#)[Help](#)[About Us](#)

Journal of Physics: Conference Series

Country [United Kingdom](#) -  [SJR Ranking of United Kingdom](#)**Subject Area and Category** [Physics and Astronomy](#)
[Physics and Astronomy \(miscellaneous\)](#)**Publisher** [Institute of Physics](#)**Publication type** Journals**ISSN** 17426588, 17426596**Coverage** 2005-ongoing**Scope** The open access Journal of Physics: Conference Series (JPCS) provides a fast, versatile and cost-effective proceedings publication service.[Homepage](#)[How to publish in this journal](#)[Contact](#)[Join the conversation about this journal](#)

65

H Index

Online Conference

Call for participation to 23rd International Conference on Multidisciplinary Studies


[euser.org](#)

OPEN

Quartiles



Physics and Astronomy (miscellaneous)











SJR



Citations per document





R **Rose** 2 months ago

Dear SCImago Team,


It is stated in the JPCS homepage that the journal is a proceeding publication

The users of Scimago Journal & Country Rank have the possibility to dialogue through comments linked to a specific journal. The purpose is to have a forum in which general doubts about the processes of publication in the journal, experiences and other issues derived from the publication of papers are resolved. For topics on particular articles, maintain the dialogue through the usual channels with your editor.

Developed by:



Powered by:



Follow us on @ScimagoJR

Scimago Lab, Copyright 2007-2020. Data Source: Scopus®

EST MODUS IN REBUS

Horatio (Satire 1.1.106)

Lipid production from tapioca wastewater by culture of *Scenedesmus sp.* with simultaneous BOD, COD and nitrogen removal

Romaidi^{1*}, Muhammad Hasanudin¹, Khusnul Kholifah¹, Alik Maulidiyah², Sapto P. Putro², Akira Kikuchi^{3,4}, Toshifumi Sakaguchi⁵

¹Department of Biology, Faculty of Science and Technology, Universitas Islam Negeri Maulana Malik Ibrahim Malang, Indonesia

²Faculty of Science and Mathematics, Diponegoro University, Semarang, Indonesia

³Faculty of Agriculture, University of Brawijaya, Malang, Indonesia

⁴Institute of Environmental and Water Resource Management, Universiti Teknologi Malaysia (UTM)

⁵Faculty of Environmental and Life Science, Prefectural University of Hiroshima, Japan

*Corresponding's author: romaidi@bio.uin-malang.ac.id

Abstract. The use of microalgae to produce biodiesel or possibly remove nutrients from industrial wastewater has gained important attention during recent years due to their photosynthetic rate and its versatile nature to grow in various wastewater systems. In this study, a microalgae, *Scenedesmus sp.*, was cultured to enhance the lipid production and nutrients removal from tapioca wastewater sample. To assess lipid production, *Scenedesmus sp.* was cultured in different concentration of tapioca wastewater sample (from 0 to 100 %), and nutrient removal including BOD, COD, NH₄, NO₂, NO₃ level by *Scenedesmus sp.* was assessed in 100% of tapioca wastewater culture. After 8 days of culture, it was found out that 50% of tapioca wastewater sample resulted in highest concentration of lipid content than that of the other concentrations. The level of environment indicator as nutrient removal such as BOD, COD, NH₄, NO₂, NO₃ were also decreased up to 74%, 72%, 95%, 91%, and 91%, respectively. The pH condition changed from initial condition acidic (pH: 4) to neutral or basic condition (pH: 7-8) as recommended in wastewater treatment system. This research provided a novel approach and achieved efficient simultaneous lipid production and nutrients removal from tapioca wastewater sample by *Scenedesmus*'s culture system.

Keyword: *Scenedesmus sp.*, tapioca wastewater, lipid production

1. Introduction

The energy crisis is one of the most important problems faced by all people over the world in the 21st century. The highest consumption of fossil fuels has result in greenhouse effect and causes global climate change [1,2]. One of a type of renewable energy is microalgae biomass-based biofuel, which is considered as one of the most potent substitutes for fossil fuel [2]. However, to increase the production of microalgae biomass, several strategies should be developed, such as modification of culture medium and environmental factors. Hence, one of promising strategies is using wastewater sample as





THE MINISTRY OF RESEARCH, TECHNOLOGY AND HIGHER EDUCATION
THE REPUBLIC OF INDONESIA

DIPONEGORO UNIVERSITY
FACULTY OF SCIENCE AND MATHEMATICS



CERTIFICATE

Decree of Dean Number : 1440/UN7.5.8/HK/2017

This is to certify that

Sriatun

as

PRESENTER

In the 7th International Seminar on New Paradigms and Innovation of Natural Science and Its Application (ISNPINSA-7) held on 17 October 2017 at Grand Candi Hotel Semarang Indonesia

with paper entitled as follows:

Zeolite / magnetite composites as catalysts on the synthesis of methyl esters (MES) from cooking oil

DEAN OF FSM UNDIP



Prof. Dr. Widowati, S.Si, M.Si.

NIP. 195902141994032002

7th ISNPINSA COMMITTEE,
CHAIRMAN



Dr. Budi Warsito, S.Si, M.Si.

NIP. 197508241999031003

Zeolite/magnetite composites as catalysts on the Synthesis of Methyl Esters (MES) from cooking oil

Sriatun¹, Adi Darmawan¹, Sriyanti¹, Wuri Cahyani¹, Hendri Widyandari²

¹) Department of Chemistry, Faculty of Science and Mathematics, Diponegoro University

²) Department of Physics Faculty of Science and Mathematics, Diponegoro University
Jl. Prof. Soedharto, SH, Tembalang, Semarang 50275, Indonesia

E-mail: sriatun@live.undip.ac.id

Abstract. The using of zeolite/magnetite composite as a catalyst for the synthesis of methyl esters (MES) of cooking oil has been performed. In this study the natural magnetite was extracted from the iron sand of Semarang marina beach and milled by high energy Milling (HEM) with ball: magnetite ratio: 1:1. The composites prepared from natural zeolite and natural magnetite with zeolite: magnetite ratio 1:1; 2:1; 3:1 and 4:1. Preparation of methyl ester was catalyzed by composite of zeolite/magnetite through transesterification reaction, it was studied on variation of catalyst concentration (w/v) 1%, 3%, 5% and 10% to feed volume. The reaction product are mixture of methyl Oleic (MES), methyl Palmitic (MES) and methyl Stearic (MES). Character product of this research include density, viscosity, acid number and iodine number has fulfilled to SNI standard 7182: 2015.

Keywords: composite, zeolite/magnetite, catalyst, MES

1. Introduction

Increased transportation demand leads to an increase in energy demand globally. Transportation sector is a sector that consumes the most energy, so it can increase environmental emission. Transportation using fuel oil is mainly processed petroleum products, while the world's oil reserves and Indonesia began to thin out. In an effort to find solutions to these problems, various studies reveal the existence of a variety of raw materials from renewable resources capable of being processed into a more environmentally friendly fuel as it reduces CO₂ emissions.

Methyl esters are a major component of biodiesel which is the most appropriate solution to replace the fuel fossils as the world's major source of energy transport, because biodiesel is a material fuel that can replace petrol diesel on a machine. Biodiesel is consisting of a mixture of mono-alkyl esters of long chain fatty acids, which are used as an alternative to fuel from diesel engines. Biodiesel or methyl esters are obtained from the transesterification of animal fats, vegetable oils, and even cooking oil waste, with catalytic process [1].

Actually Vegetable oil has a calorific value that is almost the same with conventional fuel, but usage directly as fuel is still encountered obstacles. When compared to biodiesel, vegetable oils have a much higher viscosity value at temperature 40°C. This may cause problems in the pumping and spraying process when they used as fuel [2]. The incandescent point (flash point) also much larger than diesel oil, this is it inhibit the injection process and result incomplete combustion. The use of oil



vegetable as a fuel also leaves residue carbon in the engine injector. Efforts to reduce viscosity and flash point vegetable oils, among others, by dilution of oil with solvents, emulsification, pyrolysis, and transesterification. The transesterification process is the most common way done because it does not require energy and temperature tall one. This reaction will produce methyl or ethyl esters, depending on the type of alcohol reacted. Methanol is used more as a source of alcohol because the chain is shorter, more polar and the price cheaper than other alcohols [3].

Both homogeneous and heterogeneous catalysts can be used in transesterification reactions. Basic homogeneous catalysts such as KOH as well as sodium and potassium alkoxide [3], NaOH [4], while acidic ones such as sulfuric acid, sulfonic acid and hydrochloric acid are usually used as catalysts in transesterification reactions. The using of homogeneous catalysts has a disadvantage that is difficulty in the separation of methyl ester products. The lack of homogeneous catalysts can be overcome by using a heterogeneous catalyst that is a solid catalyst, because many advantages are obtained when transesterification reactions apply the use of heterogeneous catalysts such as catalysts easily separated from the product, not corrosive and safer and more environmentally friendly [5-7]. Researches on heterogeneous/solid catalysts has been performed such as alkaline or alkaline earth oxides, alkali metals, zeolites, hydrotalcites [8-12], CaO [13], natural bentonite-supported CaO [14].

Zeolite is a porous material widely used as a catalyst based on its properties that have Bronsted acid sites and Lewis acid sites contained in pore zeolite. However, zeolites have less optimum activity and selectivity to convert reactants into desired products. Therefore we need an active phase that can minimize the less expected conditions. The widely used active phases are generally metals or metal oxides. The utilization of natural zeolite as catalyst support for transesterification of palm oil has reported. In the research, KOH was supported into natural zeolite [15]. In this work used magnetite (Fe_3O_4). Magnetite is in great demand as a catalyst because of its biocompatibility, stability, large surface area, and super paramagnetic properties [16]. Magnetite (Fe_3O_4) and $\gamma\text{-Fe}_2\text{O}_3$ which had spiral structure are used to improve biodiesel production [17]. However the magnetite embedded in zeolite as a catalyst in the transesterification reaction of used cooking oil has not been reported. As we know that in the Central Java region has great natural resource potential that is natural zeolite that found in Bayat Klaten area and iron sand/magnetite which is contained in sand of Marina Semarang beach. Therefore, in this research the utilization of both materials as raw material to preparation composite zeolite/magnetite. Furthermore the composite was applied as a catalyst for the transesterification reaction of used cooking oil to produce methyl esters.

2. Experimental Method

2.1. Materials

Sand from Marina beach Semarang, natural zeolite from Bayat Klaten. Both areas are located in Central Java, used cooking oil. Fluoric acid p.a, methanol absolute, polyethylenglycol (PEG) 4000 p.a reagents were supplied by Merck.

2.2. Instruments

X-ray diffraction (XRD) Rigaku Multiplex with Cu $K\alpha$ radiation ($\lambda = 1.54184 \text{ \AA}$) at generator voltage 40 kV and current 40 mA. Scanning Electron Microscopy (SEM) JEOL, JED 2300. GCMS-TQ8030 Shimadzu Serial O207051.

2.3. Preparation zeolite/magnetite composite catalyst

Zeolite as catalyst support was prepared by activation of natural zeolite from Bayat Klaten using HF 1% solution. The activated zeolite washing until it reaches a neutral pH, then dried to a constant weight. Characterization using XRD is used to determine the constituent components and the structure of material. Magnetite was prepared by extraction method of sand from marina beach. Treatment by using HEM-3D (High energy milling) method with planetary ball milling is used to purify and reduce the size of magnetite particles. The mass ratio of magnetite:ball was 1:1, speed 400 rpm for 5 h. The milled magnetite characterized by X-ray Diffraction (XRD) and Scanning Electron Microscopy

(SEM). The catalyst of zeolite/magnetite composite was prepared in a way activated natural zeolite was mixed with milled magnetite (Fe_3O_4). The various of zeolite:magnetite ratio mass were 1:1, 2:1, 3:1 and 4:1. The next step, addition of aquadest to the mixture and stirred in a magnetic stirrer at room temperature at 1200 rpm. An amount of PEG 4000 solution as binder was slowly added suspension. The product was dried and characterized by X-ray Diffraction (XRD).

2.4. Application zeolite/magnetite composite as transesterification catalyst

Catalytic activity tests of catalyst to transesterification reaction with used cooking oil as feed. Previously step the used cooking oil are filtered to eliminate impurities and heated to remove the water. Transesterification of used cooking oil in excess methanol (v/v) (1:12) by composite catalyst was carried out at 60°C for 4 hours. The concentration variations of catalyst were 1%, 3%, 5% and 10% (w/v). The resulting product is separated in a separating funnel for 8 hours to form 2 layers. The top layer was methyl ester and the bottom layer was glycerol. The top layer is separated and evaporated to remove the excess methanol which not participate in reaction. Furthermore, the components of the product transesterification were determined by gas chromatography mass spectrometry (GC-MS). Besides that the physical characters such as density, viscosity, acid number, iodine number and content of water also determined. Product methyl ester is weighed.

3. Results and Discussions

3.1. Characterization of zeolite/magnetite composite catalyst

Zeolite activation is done by using fluoric acid. HF solution is selected for zeolite activation because HF only slightly lowers the radius of the zeolite pores, so the radius of zeolite is still large enough and easy to do further modification. The aim of activation by fluoric acid to form decationation that influenced the zeolite surface area to increase due to the decrease of impurity covering the pores of zeolite. The increase of surface area are needed, therefore the catalytic performance of zeolite as catalyst support can be more optimal. The activation process causing the skeleton of zeolite easy to substitute with metal.

The X-ray diffraction of activated natural zeolite shown in table 1. The highest intensity peak is at $2\theta = 25.56^\circ$. Identification of peaks mordenite minerals in activated natural zeolites was matched with JCPDS 6-239 data while clinoptilolite minerals were matched with JCPDS data 39-1383 as shown in the Table 1.

Table 1. XRD data of activated natural

Component	2θ Standart (deg)	2θ observed (deg)
Mordenite JCPDS 6-239	13.2	13.36
	19.7	19.52
	25.7	25.56
	27.7	27.62
Clinoptilolite JCPDS 39-1383	22.1	22.18
	26.6	26.54
	29.9	29.98

The effect of the separation using permanent magnet can be seen in figure 1. It is clearly difference in color and size of the iron sand.



Figure 1. The difference of magnetite appearance

Extracted materials from sand is magnetite/iron sand has more dark color. This is due to the reduction of impurities from the iron sand. After milling treatment using HEM-3D, it appears that magnetite has a finer size than before the HEM-3D process. The diminished magnetic particle size results in increased surface area, where it is necessary to enlarge sites that react with feeds. The evidence of magnetite in milled material can be seen in Table 2.

Table 2. The 2 θ XRD data of milled material

Component	2 θ Standart (deg)	2 θ observed (deg)
Magnetite JCPDS 89-4319	30.083	30.093
	35.434	35.462
	43.064	43.099
	56.949	56.981
	62.536	62.592

The catalytic performance of the magnetite will be affected by the high magnetite surface area. However, due to the small particle size, agglomeration often occurs if the catalyst applied at high temperature. Therefore, magnetite particles supported in the zeolite matrix to prepare composite zeolite/magnetite as a heterogeneous catalyst. This step is expected can be improve both catalytic properties at the transesterification stage in the preparation of methyl esters from used cooking oil. The presence of magnetite in composite that the magnetic properties is expected to facilitate the separation so as to prevent the formation of hydrogen bonds so as to reduce the purity of glycerol. The evidence showing the composite has been formed on Table 3.


Table 3. The 2 θ XRD data of composite

Component	2 θ Standart (deg)	2 θ observed (deg)
Mordenite JCPDS 6-239	13.2	-
	19.7	-
	25.7	25.6
	27.7	27.54
Clinoptilolite JCPDS 39-1383	22.1	22.14
	26.6	26.58


	29.9	28.22
Magnetite	30.083	30.1
JCPDS 89-4319	35.434	35.46
	43.064	43.12
	56.949	56.92
	62.536	62.56

3.2. Structure morphology of magnetite

A slightly difference was observed in surface structure of the appearance of the magnetite and after treatment by HEM-3D. The magnetite extracted from the sand shows the area of crystals or magnetite particles appear less clear and regular. In addition, the images in Figure 2 also reveal that the material still contains impurities. While on the magnetite of treatment with HEM-3D has a crystal or particles with the edge specified. From the figure 2 also investigated that the particle size of milled magnetite seems more smooth and homogeneous. It indicates that the milling treatment using a planetary ball mill (high energy milling/HEM-3D) causing a very strong collision between the magnetite particles and the spheres/balls on the planetary ball mill, therefore reducing on magnetite particles size.



Magnetite before HEM-3D treatment



Milled magnetite with HEM-3D

Figure 2. SEM images of magnetite

3.3. Zeolite/magnetite composite as catalyst in transesterification reaction

In this transesterification reaction, triglycerides in used cooking oil react with methanol to produce methyl esters and glycerol. This reaction will more quickly achieve equilibrium with the addition of a catalyst. In biodiesel (methyl ester) synthesis, methanol is mostly used as alcohol because of its low cost, availability and production of alkyl esters with lower viscosity [18]. In this research, transesterification reaction of used cooking oil with methanol was catalyzed by zeolite/magnetite composite as heterogeneous catalysts. This composite were formed from zeolite superseded by magnetite. The use of this zeolite/magnetite composite as heterogenous catalyst will be more effectively used in transesterification reactions because it has two active sites of zeolite and magnetite that work simultaneously and for faster triglyceride splitting. Furthermore, this is because the zeolite/magnetite catalyst has two catalytically active sites namely the active site of zeolite in the form of Brønsted acid and the active site of the magnetite in the form of oxide. The Brønsted acid in this zeolite initiates triglycerides to convert the C = O bond to a C-OH bond because the Brønsted acid is able to attack the C = O bond to the C-OH bond. Whereas in this magnetite the iron oxide FeO will bind to methanol.

Based on GC-MS analysis, its known that in this transesterification reaction produce methyl ester compounds.




Figure 3. Chromatogram GC of transesterification product

Figure 3 shows the chromatogram GC of transesterification product. Moreover, fragmentation using mass spectroscopy (MS) indicates the presence of methyl esters in the reaction product. Methyl ester of transesterification product without catalyst produces methyl oleic/9-octadecanoic acid ($m/z = 296$) compound which is the highest peak fragmentation compound followed by methyl palmitic/hexadecanoic acid ($m/z = 270$) and Methyl stearic/octadecanoic acid ($m/z = 270$), meanwhile the using of concentration 1% ZM (zeolite/magnetite composite) catalyst resulted the methyl Palmitat ($m/z = 270$) as the highest peak fragmentation compound followed by methyl Oleic ($m/z = 296$). For concentration 10% ZM catalyst produces the methyl oleic ($m/z = 296$) compound which is the highest peak fragmentation followed by Methyl palmitic ($m/z = 270$).

The influence of the catalyst concentration ranging 1-10 % (w/v) on the transesterification of the used cooking oil is presented in Figure 4. The Fig. 4 shows transesterification reaction efficiency to yielded methyl ester strongly depends upon the catalyst amount, therefore increasing of the catalyst amount would increases the yield percentage. However, utilization of zeolite/magnetite composite catalyst in large amount less effective precisely because the content of water in methyl ester product is

too great. It beyond which no considerable change in oil conversion is observed due to increasing the viscosity of the mixture. Mansir [19] reveals that catalytic conversion of triglycerides to biodiesel/methyl ester involves the use of catalyst which lowers the activation energy and speeds up the reaction. In this process, the amount of catalyst utilized affects the biodiesel content. Usually biodiesel production reaction involves the use of catalyst. Lower catalyst loading is applied in the initial stage of the reaction and the conversion yield of biodiesel is measured. The subsequent catalyst loading will be increased periodically at constant reaction parameters until optimum biodiesel content from a particular feedstock is observed.




Figure 4. Correlation between Yield of methyl ester and catalyst concentration

3.4. The properties of methyl ester as transesterification product

Investigation of the product of transesterification addressed to its physical properties. The physical properties include density, viscosity, acid number, iodine number and water content. The properties should be determined because reflecting the quality of the methyl ester. Hence it can be decided whether the methyl ester is feasible as a fuel substitute or not.

3.4.1. Density. Density methyl ester as a product from transesterification reaction using various catalyst presents in Figure 5.




Figure 5. Density of methyl ester using various of catalyst

In Fig. 5 can observe the effect of zeolite/magnetite catalyst concentration to the density of methyl ester. The using of zeolite only, magnetite or composite zeolite/magnetite catalyst causes the density decreased sharply. At various concentrations of catalysts the use of composite catalysts showed less

density than zeolite or magnetite only as catalyst. This suggests that composite catalysts are more effective because of the role of multiple active sites derived in magnetite (Fe_3O_4) as acid sites that initiate reactions with methanol and acid-active sites in zeolite. In all variations of concentration catalyst the range 1-10%, composite which was synthesized by zeolite/magnetite ratio 2:1 shows the lowest density.

3.4.2. Viscosity. The viscosity of methyl ester often called kinematic viscosity is the value of methyl ester treacly as fuel at 40°C . Viscosity of methyl ester as a product from transesterification using various catalyst presents in Figure 6.




Figure 6. Viscosity of methyl ester using various of catalyst

Viscosity is one of the important properties that must be known if the methyl esters are used instead of fuels. This is because these properties correlate with their performance on the machine. When overly high viscosity will make the fuel become larger droplets that will result in a deposit on the machine, however if the viscosity is too low it will produce a spray that is too smooth to form a rich zone that causes the formation of soot [20]. The role of the catalyst in influencing the viscosity properties has a tendency similar to that of the methyl ester density. Hence in all variations of concentration catalyst the range 1-10%, composite which was synthesized by zeolite/magnetite ratio 2:1 shows the lowest viscosity.

3.4.3. Acid number. The acid number is milligram amount of KOH needed for neutralized 1 gram of sample. The acid number is calculated from the percentage value of fatty acids free. The acid number of methyl ester as a product from transesterification using various catalyst presents in Figure 7.




Figure 7. Viscosity of methyl ester using various of catalyst

Large acid numbers show large free fatty acids derived from oil hydrolysis or due to poor processing. The higher the acid number the lower the quality. In this work, the catalyst plays a very significant role in decreasing the acid number. In all variations of concentration catalyst the range 1-10%, composite which was synthesized by zeolite/magnetite ratio 2:1 shows the lowest acid number. When the reaction using zeolite/magnetite ratio 2:1 composite as catalyst cause the acid number increasing slightly. This data reveals that the need for magnetite in assisting the process of initiation of reactions between feeds and methanol.

3.4.4. Iodine number. The iodine number called iodine absorption number is the mass of iodine in grams absorbed at 100 grams of a chemical under the test conditions used. Iodine numbers are often used to determine the amount of unsaturation in fatty acids. The unsaturation is in the form of a double bond, which will react with the iodine compound. The higher the iodine number, the more the C = C bonds present in the fat [21]. Iodine number of methyl ester as a product from transesterification using various catalyst presents in Figure 8.




Figure 8. Iodine number of methyl ester using various of catalyst

The higher the iodine value, the higher the number of double-bonded fatty acids contained in the methyl ester. The more double bonds held in the sample have greater potential to experience the polymerization process due to lower stability. The influence of the rise of methyl ester unsaturation can cause CO₂ gas to increase the degree of unsaturation associated with the iodine number. The longer the carbon chain the lower the CO₂ emissions and the higher the iodine number the lower the CO₂ emissions produced [20]. If the methyl ester would be use as biofuel so the number of iodine must

be low. Therefore based on the data in Fig. 8, the low iodine number is belonged by methyl esters of transesterified results catalyzed by zeolites. The explanation argument for this fact is that iodine is most likely absorbed by the pores of the zeolite, where it cannot occur in magnetite because magnetite is not a porous material. This is also cause the highest iodine number on magnetite catalyst. The ability adsorption of zeolite is reduced when zeolite compose with magnetite.

3.4.5. Water content. Water content is the difference of weight methyl ester before and after evaporating. In this work data of water content in methyl ester presents in Figure 9. In this data there is a tendency on catalyst has similarity of role with the viscosity data. This means that the lowest water content in the use of catalysts only zeolite, and the highest water content in magnetite. The role of the pores present in the zeolite structure absorb the water, therefore the catalyst having relatively high porosity as in the zeolite/magnetite 3: 1 composite also shows a low water content.




Figure 9. The water content of methyl ester using various of catalyst

4. Conclusion

Preparation of methyl ester was catalyzed by composite of zeolite/magnetite through transesterification reaction using variation of catalyst concentration 1%, 3%, 5% and 10% (w/v) produce a mixture of methyl Oleic (MES) Palmitic Acid (MES) and Stearic Acid (MES). Character product such as density, viscosity, acid number and iodine number has fulfilled to SNI standard 7182: 2015.

Acknowledgment

This research financial support by funding of Besides APBN DPA SUKPA LPPM Diponegoro University, Fiscal Year 2017. We convey gratefully to Chemistry Departement for the facilities to carry out this research.

References

- [1] Srivastava, A., Prasad, R., 2000, *Renewable and Sustainable Energy Reviews*, **4** (2), 111-133.
- [2] Sinha, S., Agarwal, A.K., Garg, S., 2008, *Energy Conversion and Management*, **49** (5), 1248-1257.
- [3] Ma, F., Hanna, M.A., 1999, *Bioresource Technology*, **70** (1), 1-15.
- [4] Keera, S.T., El Sabagh, S.M., Taman, A.R., 2011, *Fuel*, **90** (1), 42-47.
- [5] Kumar, M., Sharma, M.P., 2016, *Renewable and Sustainable Energy Reviews*, **56**, 1129-1138.
- [6] Wang, J.X., Chen, K.T., Wu, J.S., Wang, P.H., Huang, S.T., Chen, C.C., 2012, *Fuel Processing Technology*, **104**, 167-173.
- [7] Dai, Y.M., Chen, K.T., Wang, P.H., Chen, C.C., 2016, *Advanced Powder Technology*, **27** (6), 2432-2438.
- [8] Lu, Y., Zhang, Z., Xu, Y., Liu, Q., Qian, G., 2015, *Bioresource Technology*, **190**, 438-441.

- [9] Amani, H., Ahmad, Z., Hameed, B.H., 2014, *Applied Catalysis A*, **487**, 16-25.
- [10] Paterson, G., Issariyakul, T., Baroi, C., Bassi, A., Dalai, A., 2013, *Catalysis Today*, **212**, 157-163.
- [11] Dai, Y.M., Kao, I.H., Chen, C.C., 2017, *Journal of Taiwan Institute of Chemical Engineers*, **70**, 260-266.
- [12] Habaki, H., Hayashi, T., Egashira, R., 2014, *Journal of Environmental Chemical Engineering*, **2** (3), 1543-1550.
- [13] Kouzu, M., Hidaka, J., 2012, *Fuel*, **93**, 1-2.
- [14] Shan, R., Zhao, C., Yuan, H., Wang, S.X., 2017, *Energy Conversion and Management*, **138**, 547-555.
- [15] IndraKusuma, R., Hadinoto, J.P., Ayucitra, A., Soetaredjo, F.E., Ismadji, S., 2013, *Applied Clay Science*, **74**, 121-126.
- [16] Lu, A.H., Salabas, E.E.L., Schüth, F., 2007, *Angewandte Chemie International Edition* **46** (8), 1222-1244.
- [17] Teja A.S. and Koh, P.Y., 2009, *Progress in crystal growth and characterization of materials* **55** (1), 22-45.
- [18] Wittcoff, H.A., Reuben, B.G., 1996, *Industrial organic chemicals*, John Wiley & Sons, New York.
- [19] Mansir, N., Taufiq-Yap, Y.H., Rashid, U., Lokman, I.M., 2017, *Energy Conversion and Management*, **141**, 171-182.
- [20] Prihandana R. and Hendroko, R., 2008, *Energi Hijau: Pilihan Bijak Menuju Negeri Mandiri Energi*, Niaga Swadaya.
- [21] Thomas, A., 2002, *Fats and Fatty Oils*, Ullmann's Encyclopedia of Industrial Chemistry, Weinheim: Wiley-VCH.

Zeolitemagnetite composites as catalysts on the Synthesis of Methyl Esters (MES) from cooking oil

by Sariatun Sariatun

Submission date: 25-May-2019 08:10AM (UTC+0700)

Submission ID: 1135637183

File name: lysts_on_the_Synthesis_of_Methyl_Esters_MES_from_cooking_oil.pdf (776.43K)

Word count: 4468

Character count: 23535

PAPER ⁴ OPEN ACCESS

Zeolite/magnetite composites as catalysts on the Synthesis of Methyl Esters (MES) from cooking oil

³

To cite this article: Sriatun *et al* 2018 *J. Phys.: Conf. Ser.* **1025** 012135

View the [article online](#) for updates and enhancements.



IOP | ebooks™

Bringing you innovative digital publishing with leading voices
to create your essential collection of books in STEM research.

Start exploring the collection - download the first chapter of
every title for free.

4

Zeolite/magnetite composites as catalysts on the Synthesis of Methyl Esters (MES) from cooking oil

Sriatun¹, Adi Darmawan¹, Sriyanti¹, Wuri Cahyani¹, Hendri Widyandari²

¹) Department of Chemistry, Faculty of Science and Mathematics, Diponegoro University

²) Department of Physics Faculty of Science and Mathematics, Diponegoro University
Jl. Prof. Soedharto, SH, Tembalang, Semarang 50275, Indonesia

E-mail: sriatun@live.undip.ac.id

Abstract. The using of zeolite/magnetite composite as a catalyst for the synthesis of methyl esters (MES) of cooking oil has been performed. In this study the natural magnetite was extracted from the iron sand of Semarang marina beach and milled by high energy Milling (HEM) with ball: magnetite ratio: 1:1. The composites prepared from natural zeolite and natural magnetite with zeolite: magnetite ratio 1:1; 2:1; 3:1 and 4:1. Preparation of methyl ester was catalyzed by composite of zeolite/magnetite through transesterification reaction, it was studied on variation of catalyst concentration (w/v) 1%, 3%, 5% and 10% to feed volume. The reaction product are mixture of methyl Oleic (MES), methyl Palmitic (MES) and methyl Stearic (MES). Character product of this research include density, viscosity, acid number and iodine number has fulfilled to SNI standard 7182: 2015.

Keywords: composite, zeolite/magnetite, catalyst, MES

1. Introduction

Increased transportation demand leads to an increase in energy demand globally. Transportation sector is a sector that consumes the most energy, so it can increase environmental emission. Transportation using fuel oil is mainly processed petroleum products, while the world's oil reserves and Indonesia began to thin out. In an effort to find solutions to these problems, various studies reveal the existence of a variety of raw materials from renewable resources capable of being processed into a more environmentally friendly fuel as it reduces CO₂ emissions.

Methyl esters are a major component of biodiesel which is the most appropriate solution to replace the fuel fossils as the world's major source of energy transport, because biodiesel is a material fuel that can replace petrol diesel on a machine. Biodiesel is consisting of a mixture of mono-alkyl esters of long chain fatty acids, which are used as an alternative to fuel from diesel engines. Biodiesel or methyl esters are obtained from the transesterification of animal fats, vegetable oils, and even cooking oil waste, with catalytic process [1].

Actually Vegetable oil has a calorific value that is almost the same with conventional fuel, but usage directly as fuel is still encountered obstacles. When compared to biodiesel, vegetable oils have a much higher viscosity value at temperature 40°C. This may cause problems in the pumping and spraying process when they used as fuel [2]. The incandescent point (flash point) also much larger than diesel oil, this is it inhibit the injection process and result incomplete combustion. The use of oil



Content from this work may be used under the terms of the Creative Commons Attribution 3.0 licence. Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI.

Published under licence by IOP Publishing Ltd

vegetable as a fuel also leaves residue carbon in the engine injector. Efforts to reduce viscosity and flash point vegetable oils, among others, by dilution of oil with solvents, emulsification, pyrolysis, and transesterification. The transesterification process is the most common way done because it does not require energy and temperature tall one. This reaction will produce methyl or ethyl esters, depending on the type of alcohol reacted. Methanol is used more as a source of alcohol because the chain is shorter, more polar and the price cheaper than other alcohols [3].

Both homogeneous and heterogeneous catalysts can be used in transesterification reactions. Basic homogeneous catalysts such as KOH as well as sodium and potassium alkoxide [3], NaOH [4], while acidic ones such as sulfuric acid, sulfonic acid and hydrochloric acid are usually used as catalysts in transesterification reactions. The using of homogeneous catalysts has a disadvantage that is difficulty in the separation of methyl ester products. The lack of homogeneous catalysts can be overcome by using a heterogeneous catalyst that is a solid catalyst, because many advantages are obtained when transesterification reactions apply the use of heterogeneous catalysts such as catalysts easily separated from the product, not corrosive and safer and more environmentally friendly [5-7]. Researches on heterogeneous/solid catalysts has been performed such as alkaline or alkaline earth oxides, alkali metals, zeolites, hydrotalcites [8-12], CaO [13], natural bentonite-supported CaO [14].

Zeolite is a porous material widely used as a catalyst based on its properties that have Bronsted acid sites and Lewis acid sites contained in pore zeolite. However, zeolites have less optimum activity and selectivity to convert reactants into desired products. Therefore we need an active phase that can minimize the less expected conditions. The widely used active phases are generally metals or metal oxides. The utilization of natural zeolite as catalyst support for transesterification of palm oil has reported. In the research, KOH was supported into natural zeolit [15]. In this work used magnetite (Fe_3O_4). Magnetite is in great demand as a catalyst because of its biocompatibility, stability, large surface area, and super paramagnetic properties [16]. Magnetite (Fe_3O_4) and $\gamma\text{-Fe}_2\text{O}_3$ which had spiral structure are used to improve biodiesel production [17]. However the magnetite embedded in zeolite as a catalyst in the transesterification reaction of used cooking oil has not been reported. As we know that in the Central Java region has great natural resource potential that is natural zeolite that found in Bayat Klaten area and iron sand/magnetite which is contained in sand of Marina Semarang beach. Therefore, in this research the utilization of both materials as raw material to preparation composite zeolite/magnetite. Furthermore the composite was applied as a catalyst for the transesterification reaction of used cooking oil to produce methyl esters.

2. Experimental Method

2.1. Materials

Sand from Marina beach Semarang, natural zeolite from Bayat Klaten. Both areas are located in Central Java, used cooking oil. Fluoric acid p.a, methanol absolute, polyethylenglycol (PEG) 4000 p.a reagents were supplied by Merck.

2.2. Instruments

X-ray diffraction (XRD) Rigaku Multiplex with Cu K α radiation ($\lambda = 1.54184 \text{ \AA}$) at generator voltage 40 kV and current 40 mA. Scanning Electron Microscopy (SEM) JEOL, JED 2300. GCMS-TQ8030 Shimadzu Serial O207051.

2.3. Preparation zeolite/magnetite composite catalyst

Zeolite as catalyst support was prepared by activation of natural zeolite from Bayat Klaten using HF 1% solution. The activated zeolite washing until it reaches a neutral pH, then dried to a constant weight. Characterization using XRD is used to determine the constituent components and the structure of material. Magnetite was prepared by extraction method of sand from marina beach. Treatment by using HEM-3D (High energy milling) method with planetary ball milling is used to purify and reduce the size of magnetite particles. The mass ratio of magnetite:ball was 1:1, speed 400 rpm for 5 h. The milled magnetite characterized by X-ray Diffraction (XRD) and Scanning Electron Microscopy

(SEM). The catalyst of zeolite/magnetite composite was prepared in a way activated natural zeolite was mixed with milled magnetite (Fe_3O_4). The various of zeolite:magnetite ratio mass were 1:1, 2:1, 3:1 and 4:1. The next step, addition of aquadest to the mixture and stirred in a magnetic stirrer at room temperature at 1200 rpm. An amount of PEG 4000 solution as binder was slowly added suspension. The product was dried and characterized by X-ray Diffraction (XRD).

2.4. Application zeolite/magnetite composite as transesterification catalyst

Catalytic activity tests of catalyst to transesterification reaction with used cooking oil as feed. Previously step the used cooking oil are filtered to eliminate impurities and heated to remove the water. Transesterification of used cooking oil in excess methanol (v/v) (1:12) by composite catalyst was carried out at 60°C for 4 hours. The concentration variations of catalyst were 1%, 3%, 5% and 10% (w/v). The resulting product is separated in a separating funnel for 8 hours to form 2 layers. The top layer was methyl ester and the bottom layer was glycerol. The top layer is separated and evaporated to remove the excess methanol which not participate in reaction. Furthermore, the components of the product transesterification were determined by gas chromatography mass spectrometry (GC-MS). Besides that the physical characters such as density, viscosity, acid number, iodine number and content of water also determined. Product methyl ester is weighed.

3. Results and Discussions

3.1. Characterization of zeolite/magnetite composite catalyst

Zeolite activation is done by using fluoric acid. HF solution is selected for zeolite activation because HF only slightly lowers the radius of the zeolite pores, so the radius of zeolite is still large enough and easy to do further modification. The aim of activation by fluoric acid to form decationation that influenced the zeolite surface area to increase due to the decrease of impurity covering the pores of zeolite. The increase of surface area are needed, therefore the catalytic performance of zeolite as catalyst support can be more optimal. The activation process causing the skeleton of zeolite easy to substitute with metal.

The X-ray diffraction of activated natural zeolite shown in table 1. The highest intensity peak is at $2\theta = 25.56^\circ$. Identification of peaks mordenite minerals in activated natural zeolites was matched with JCPDS 6-239 data while clinoptilolite minerals were matched with JCPDS data 39-1383 as shown in the Table 1.

Table 1. XRD data of activated natural

Component	2θ Standart (deg)	2θ observed (deg)
Mordenite JCPDS 6-239	13.2	13.36
	19.7	19.52
	25.7	25.56
	27.7	27.62
Clinoptilolite JCPDS 39-1383	22.1	22.18
	26.6	26.54
	29.9	29.98

The effect of the separation using permanent magnet can be seen in figure 1. It is clearly difference in color and size of the iron sand.




Figure 1. The difference of magnetite appearance

Extracted materials from sand is magnetite/iron sand has more dark color. This is due to the reduction of impurities from the iron sand. After milling treatment using HEM-3D, it appears that magnetite has a finer size than before the HEM-3D process. The diminished magnetic particle size results in increased surface area, where it is necessary to enlarge sites that react with feeds. The evidence of magnetite in milled material can be seen in Table 2.

Table 2. The 2 θ XRD data of milled material

Component	2 θ Standart (deg)	2 θ observed (deg)
Magnetite JCPDS 89-4319	30.083	30.093
	35.434	35.462
	43.064	43.099
	56.949	56.981
	62.536	62.592

The catalytic performance of the magnetite will be affected by the high magnetite surface area. However, due to the small particle size, agglomeration often occurs if the catalyst applied at high temperature. Therefore, magnetite particles supported in the zeolite matrix to prepare composite zeolite/magnetite as a heterogeneous catalyst. This step is expected can be improve both catalytic properties at the transesterification stage in the preparation of methyl esters from used cooking oil. The presence of magnetite in composite that the magnetic properties is expected to facilitate the separation so as to prevent the formation of hydrogen bonds so as to reduce the purity of glycerol. The evidence showing the composite has been formed on Table 3.

Table 3. The 2 θ XRD data of composite

Component	2 θ Standart (deg)	2 θ observed (deg)
Mordenite JCPDS 6-239	13.2	-
	19.7	-
	25.7	25.6
	27.7	27.54
Clinoptilolite JCPDS 39-1383	22.1	22.14
	26.6	26.58

	29.9	28.22
Magnetite	30.083	30.1
JCPDS 89-4319	35.434	35.46
	43.064	43.12
	56.949	56.92
	62.536	62.56

3.2. Structure morphology of magnetite

A slightly difference was observed in surface structure of the appearance of the magnetite and after treatment by HEM-3D. The magnetite extracted from the sand shows the area of crystals or magnetite particles appear less clear and regular. In addition, the images in Figure 2 also reveal that the material still contains impurities. While on the magnetite of treatment with HEM-3D has a crystal or particles with the edge specified. From the figure 2 also investigated that the particle size of milled magnetite seems more smooth and homogeneous. It indicates that the milling treatment using a planetary ball mill (high energy milling/HEM-3D) causing a very strong collision between the magnetite particles and the spheres/balls on the planetary ball mill, therefore reducing on magnetite particles size.




Figure 2. SEM images of magnetite

3.3. Zeolite/magnetite composite as catalyst in transesterification reaction

In this transesterification reaction, triglycerides in used cooking oil react with methanol to produce methyl esters and glycerol. This reaction will more quickly achieve equilibrium with the addition of a catalyst. In biodiesel (methyl ester) synthesis, methanol is mostly used as alcohol because of its low cost, availability and production of alkyl esters with lower viscosity [18]. In this research, transesterification reaction of used cooking oil with methanol was catalyzed by zeolite/magnetite composite as heterogeneous catalysts. This composite were formed from zeolite superseded by magnetite. The use of this zeolite/magnetite composite as heterogenous catalyst will be more effectively used in transesterification reactions because it has two active sites of zeolite and magnetite that work simultaneously and for faster triglyceride splitting. Furthermore, this is because the zeolite/magnetite catalyst has two catalytically active sites namely the active site of zeolite in the form of Brønsted acid and the active site of the magnetite in the form of oxide. The Brønsted acid in this zeolite initiates triglycerides to convert the C = O bond to a C-OH bond because the Brønsted acid is able to attack the C = O bond to the C-OH bond. Whereas in this magnetite the iron oxide FeO will bind to methanol.

Based on GC-MS analysis, its known that in this transesterification reaction produce methyl ester compounds.




Figure 3. Chromatogram GC of transesterification product

Figure 3 shows the chromatogram GC of transesterification product. Moreover, fragmentation using mass spectroscopy (MS) indicates the presence of methyl esters in the reaction product. Methyl ester of transesterification product without catalyst produces methyl oleic/9-octadecanoic acid ($m/z = 296$) compound which is the highest peak fragmentation compound followed by methyl palmitic/hexadecanoic acid ($m/z = 270$) and Methyl stearic/octadecanoic acid ($m/z = 270$), meanwhile the using of concentration 1% ZM (zeolite/magnetite composite) catalyst resulted the methyl Palmitat ($m/z = 270$) as the highest peak fragmentation compound followed by methyl Oleic ($m/z = 296$). For concentration 10% ZM catalyst produces the methyl oleic ($m/z = 296$) compound which is the highest peak fragmentation followed by Methyl palmitic ($m/z = 270$).

The influence of the catalyst concentration ranging 1-10 % (w/v) on the transesterification of the used cooking oil is presented in Figure 4. The Fig. 4 shows transesterification reaction efficiency to yielded methyl ester strongly depends upon the catalyst amount, therefore increasing of the catalyst amount would increases the yield percentage. However, utilization of zeolite/magnetite composite catalyst in large amount less effective precisely because the content of water in methyl ester product is

too great. It beyond which no considerable change in oil conversion is observed due to increasing the viscosity of the mixture. Mansir [19] reveals that catalytic conversion of triglycerides to biodiesel/methyl ester involves the use of catalyst which lowers the activation energy and speeds up the reaction. In this process, the amount of catalyst utilized affects the biodiesel content. Usually biodiesel production reaction involves the use of catalyst. Lower catalyst loading is applied in the initial stage of the reaction and the conversion yield of biodiesel is measured. The subsequent catalyst loading will be increased periodically at constant reaction parameters until optimum biodiesel content from a particular feedstock is observed.




Figure 4. Correlation between Yield of methyl ester and catalyst concentration

3.4. The properties of methyl ester as transesterification product

Investigation of the product of transesterification addressed to its physical properties. The physical properties include density, viscosity, acid number, iodine number and water content. The properties should be determined because reflecting the quality of the methyl ester. Hence it can be decided whether the methyl ester is feasible as a fuel substitute or not.

3.4.1. Density. Density methyl ester as a product from transesterification reaction using various catalyst presents in Figure 5.




Figure 5. Density of methyl ester using various of catalyst

In Fig. 5 can observe the effect of zeolite/magnetite catalyst concentration to the density of methyl ester. The using of zeolite only, magnetite or composite zeolite/magnetite catalyst causes the density decreased sharply. At various concentrations of catalysts the use of composite catalysts showed less

density than zeolite or magnetite only as catalyst. This suggests that composite catalysts are more effective because of the role of multiple active sites derived in magnetite (Fe_3O_4) as acid sites that initiate reactions with methanol and acid-active sites in zeolite. In all variations of concentration catalyst the range 1-10%, composite which was synthesized by zeolite/magnetite ratio 2:1 shows the lowest density.

3.4.2. Viscosity. The viscosity of methyl ester often called kinematic viscosity is the value of methyl ester treacly as fuel at 40°C . Viscosity of methyl ester as a product from transesterification using various catalyst presents in Figure 6.




Figure 6. Viscosity of methyl ester using various of catalyst

Viscosity is one of the important properties that must be known if the methyl esters are used instead of fuels. This is because these properties correlate with their performance on the machine. When overly high viscosity will make the fuel become larger droplets that will result in a deposit on the machine, however if the viscosity is too low it will produce a spray that is too smooth to form a rich zone that causes the formation of soot [20]. The role of the catalyst in influencing the viscosity properties has a tendency similar to that of the methyl ester density. Hence in all variations of concentration catalyst the range 1-10%, composite which was synthesized by zeolite/magnetite ratio 2:1 shows the lowest viscosity.

3.4.3. Acid number. The acid number is milligram amount of KOH needed for neutralized 1 gram of sample. The acid number is calculated from the percentage value of fatty acids free. The acid number of methyl ester as a product from transesterification using various catalyst presents in Figure 7.




Figure 7. Viscosity of methyl ester using various of catalyst

Large acid numbers show large free fatty acids derived from oil hydrolysis or due to poor processing. The higher the acid number the lower the quality. In this work, the catalyst plays a very significant role in decreasing the acid number. In all variations of concentration catalyst the range 1-10%, composite which was synthesized by zeolite/magnetite ratio 2:1 shows the lowest acid number. When the reaction using zeolite/magnetite ratio 2:1 composite as catalyst cause the acid number increasing slightly. This data reveals that the need for magnetite in assisting the process of initiation of reactions between feeds and methanol.

3.4.4. Iodine number. The iodine number called iodine absorption number is the mass of iodine in grams absorbed at 100 grams of a chemical under the test conditions used. Iodine numbers are often used to determine the amount of unsaturation in fatty acids. The unsaturation is in the form of a double bond, which will react with the iodine compound. The higher the iodine number, the more the C = C bonds present in the fat [21]. Iodine number of methyl ester as a product from transesterification using various catalyst presents in Figure 8.




Figure 8. Iodine number of methyl ester using various of catalyst

The higher the iodine value, the higher the number of double-bonded fatty acids contained in the methyl ester. The more double bonds held in the sample have greater potential to experience the polymerization process due to lower stability. The influence of the rise of methyl ester unsaturation can cause CO₂ gas to increase the degree of unsaturation associated with the iodine number. The longer the carbon chain the lower the CO₂ emissions and the higher the iodine number the lower the CO₂ emissions produced [20]. If the methyl ester would be use as biofuel so the number of iodine must

be low. Therefore based on the data in Fig. 8, the low iodine number is belonged by methyl esters of transesterified results catalyzed by zeolites. The explanation argument for this fact is that iodine is most likely absorbed by the pores of the zeolite, where it cannot occur in magnetite because magnetite is not a porous material. This is also cause the highest iodine number on magnetite catalyst. The ability adsorption of zeolite is reduced when zeolite compose with magnetite.

3.4.5. Water content. Water content is the difference of weight methyl ester before and after evaporating. In this work data of water content in methyl ester presents in Figure 9. In this data there is a tendency on catalyst has similarity of role with the viscosity data. This means that the lowest water content in the use of catalysts only zeolite, and the highest water content in magnetite. The role of the pores present in the zeolite structure absorb the water, therefore the catalyst having relatively high porosity as in the zeolite/magnetite 3:1 composite also shows a low water content.




Figure 9. The water content of methyl ester using various of catalyst

4 Conclusion

Preparation of methyl ester was catalyzed by composite of zeolite/magnetite through transesterification reaction using variation of catalyst concentration 1%, 3%, 5% and 10% (w/v) produce a mixture of methyl Oleic (MES) Palmitic Acid (MES) and Stearic Acid (MES). Character product such as density, viscosity, acid number and iodine number has fulfilled to SNI standard 7182: 2015.

Acknowledgment

This research financial support by funding of Besides APBN DPA SUKPA LPPM Diponegoro University, Fiscal Year 2017. We convey gratefully to Chemistry Departement for the facilities to carry out this research.

References

- [1] Srivastava, A., Prasad, R., 2000, *Renewable and Sustainable Energy Reviews*, **4** (2), 111-133.
- [2] Sinha, S., Agarwal, A.K., Garg, S., 2008, *Energy Conversion and Management*, **49** (5), 1248-1257.
- [3] Ma, F., Hanna, M.A., 1999, *Bioresource Technology*, **70** (1), 1-15.
- [4] Keera, S.T., El Sabagh, S.M., Taman, A.R., 2011, *Fuel*, **90** (1), 42-47.
- [5] Kumar, M., Sharma, M.P., 2016, *Renewable and Sustainable Energy Reviews*, **56**, 1129-1138.
- [6] Wang, J.X., Chen, K.T., Wu, J.S., Wang, P.H., Huang, S.T., Chen, C.C., 2012, *Fuel Processing Technology*, **104**, 167-173.
- [7] Dai, Y.M., Chen, K.T., Wang, P.H., Chen, C.C., 2016, *Advanced Powder Technology*, **27** (6), 2432-2438.
- [8] Lu, Y., Zhang, Z., Xu, Y., Liu, Q., Qian, G., 2015, *Bioresource Technology*, **190**, 438-441.

- [9] Amani, H., Ahmad, Z., Hameed, B.H., 2014, *Applied Catalysis A*, **487**, 16-25.
- [10] Paterson, G., Issariyakul, T., Baroi, C., Bassi, A., Dalai, A., 2013, *Catalysis Today*, **212**, 157-163.
- [11] Dai, Y.M., Kao, I.H., Chen, C.C., 2017, *Journal of Taiwan Institute of Chemical Engineers*, **70**, 260-266.
- [12] Habaki, H., Hayashi, T., Egashira, R., 2014, *Journal of Environmental Chemical Engineering*, **2** (3), 1543-1550.
- [13] Kouzu, M., Hidaka, J., 2012, *Fuel*, **93**, 1-2.
- [14] Shan, R., Zhao, C., Yuan, H., Wang, S.X., 2017, *Energy Conversion and Management*, **138**, 547-555.
- [15] IndraKusuma, R., Hadinoto, J.P., Ayucitra, A., Soetaredjo, F.E., Ismadji, S., 2013, *Applied Clay Science*, **74**, 121-126.
- [16] Lu, A.H., Salabas, E.E.L., Schüth, F., 2007, *Angewandte Chemie International Edition* **46** (8), 1222-1244.
- [17] Teja A.S. and Koh, P.Y., 2009, *Progress in crystal growth and characterization of materials* **55** (1), 22-45.
- [18] Wittcoff, H.A., Reuben, B.G., 1996, *Industrial organic chemicals*, John Wiley & Sons, New York.
- [19] Mansir, N., Taufiq-Yap, Y.H., Rashid, U., Lokman, I.M., 2017, *Energy Conversion and Management*, **141**, 171-182.
- [20] Prihandana R. and Hendroko, R., 2008, *Energi Hijau: Pilihan Bijak Menuju Negeri Mandiri Energi*, Niaga Swadaya.
- [21] Thomas, A., 2002, *Fats and Fatty Oils*, Ullmann's Encyclopedia of Industrial Chemistry, Weinheim: Wiley-VCH.

Zeolitemagnetite composites as catalysts on the Synthesis of Methyl Esters (MES) from cooking oil

ORIGINALITY REPORT

9%

SIMILARITY INDEX

6%

INTERNET SOURCES

8%

PUBLICATIONS

5%

STUDENT PAPERS

PRIMARY SOURCES

1

Submitted to The University of the West of Scotland

Student Paper

4%

2

Nasar Mansir, Yun Hin Taufiq-Yap, Umer Rashid, Ibrahim M. Lokman. "Investigation of heterogeneous solid acid catalyst performance on low grade feedstocks for biodiesel production: A review", Energy Conversion and Management, 2017

Publication

2%

3

digilib.uinsby.ac.id

Internet Source

2%

4

china.iopscience.iop.org

Internet Source

2%

Exclude quotes

On

Exclude matches

< 2%

Exclude bibliography

On